



Freephone 0800 484181
Freefax 0800 525103

Rolled Lead Sheet
to BS EN12588
thicknesses to tolerances of $\pm 5\%$



Application by Code

Code	Thickness	Kg per M ²	Soakers	Flashings	Flat Roofing	Parapet and Tapered Valley Gutters	Pitched Roofs	Vertical Cladding	Dormers	Bay Roofs and Canopies
Code 3	1.32mm	14.97								
Code 4	1.80mm	20.41								
Code 5	2.24mm	25.4								
Code 6	2.65mm	30.05								
Code 7	3.15mm	35.72								
Code 8	3.55mm	40.26								
Ancillary products per Application			1	1, 2, 3, 4, 5, 6	1, 6, 7, 8, 9	1, 6, 7, 9, 10	1, 6, 7, 8, 9	1, 6, 7, 11	1, 6, 7, 8, 9	1, 6, 7, 8, 9

- | | | | |
|-----------------------|-------------------------|--------------------|----------------------|
| 1. Patination Oil | 4. Morton Flashing Tool | 7 Nails | 10. Expansion Joint |
| 2. Lead Sheet Sealant | 5. Morton Bolster Tool | 8. Wood Core Roll | 11. Dome Head Screws |
| 3. Flashing Wedges | 6. Clips | 9. Geotec Underlay | |

For correct fixing details refer to The Calder Guide to Good Leadwork - Visit our website @ www.calderlead.co.uk

Nobody knows more about lead than Calder!