

Glazing Options

Roof Windows


Keylite Roof Windows can be supplied with a wide range of glazing variants including thermal properties, tinted, frosted and self-cleaning glass.



Standard Glazing


Optional Glazing Upgrades

THERMAL




- ▶ 4mm toughened on outer pane.
- ▶ 20mm Argon gas filled cavity.
- ▶ 4mm float inner pane.
- ▶ Warm edge glazing unit.

HI THERM




- ▶ 4mm toughened outer pane.
- ▶ 18mm Argon gas filled cavity.
- ▶ 6mm laminated inner pane.
- ▶ Ideal safety glazing for windows below 800mm from finish floor level or windows above head height.
- ▶ Improves sound reduction, safety and a reduction in the harmful effects of UV light.
- ▶ Warm edge glazing unit.

TRIPLE



- ▶ 4mm toughened outer pane.
- ▶ 10mm Krypton gas filled cavity.
- ▶ 4mm float centre pane
- ▶ 8mm Krypton gas filled cavity.
- ▶ 4mm float inner pane
- ▶ Triple glazing offers a lower U value as well as better sound insulation.
- ▶ Warm edge glazing unit.

INTEGRAL



- ▶ 4mm toughened outer pane.
- ▶ 22mm Argon gas filled cavity. Inclusive of integral blind.
- ▶ 4mm toughened inner pane
- ▶ Provides a reduction in the harmful effects of uv light.
- ▶ Warm edge glazing unit.

NOTE: Self-cleaning glass available upon request. For further information, please contact the Keylite technical team.

NOTE: Hi-Therm and Triple glazing are not available with integral blinds. In case of Integral Blind Window, the Low 'E' Coating is on the inner surface of the outside pane. This has no detrimental effect on 'U' value. U value is based on a centre pane measurement.

Bronze



Frosted



Self Cleaning



Triple Glazing



GB

Unit 3 Gateway Road, Burton Gateway,
Burton upon Trent, DE13 8FL

T: +44 (0) 1283 200 158
E: info@keyliteuk.com

NI & ROI

Derryloran Industrial Est. Sandholes Road,
Cookstown, Co. Tyrone, BT80 9LU

T: +44 (0) 28 8675 8921
E: info@keylite.co.uk